

CONTAINER TROLLEYS

1000 x 700 mm (460 L) or 1200 x 800 mm (640 L)

500 KG

Guarantee
10 years

GALVANISED STEEL Cladding

Ideal for the picking, handling and storage of goods.

FRAME:

- Robust and entirely mechanically welded construction.
- Collapsible front half panel

TRAY:

- 16 mm thick MDF, will not split or shatter even in case of repeated impact. No risk of splinters.

ROLLING QUALITY:

- Ø 200 mm, mounted on sealed ball bearings.
- Far less effort to start off.
- TPE tyre : silent, non-staining, absorb vibration.
- Trolleys equipped with 2 fixed wheels + 2 swivel with brake compliant with EN 1757 standard.

CLADDING:

- Galvanised sheet thickness 20/10
- Usable height 700mm.
- Ergonomic push height 1090 mm.

FINISH:

- Epoxy paint makes frame very scratch resistant

SERVICE :

- Trolleys delivered READY TO USE.

STRONG POINTS

- Trolleys with roof: padlockable, they offer excellent protection for fragile goods.
- The almost total opening facilitates loading and unloading.



800 009 566
without roof



800 009 568
with roof

Reference	Model	Tray measurements (W x D) mm	Useful size (LxWxH) mm	Overall measurementd (WxDxH) mm	Wheels	Weight kg
800 009 566	without roof	1000 x 700	950 x 650 x 700	1105 x 725 x 1095	Ø 200 mm grey non-marking wheels	79
800 009 567		1200 x 800	1150 x 750 x 700	1305 x 825 x 1095		96
800 009 568	with roof	1000 x 700	950 x 650 x 700	1105 x 725 x 1095		94
800 009 569		1,200 x 800	1150 x 750 x 700	1305 x 825 x 1095		115

OTHER MODELS AVAILABLE



MESH Cladding



Wood cladding



Steel sheet cladding

OPTIONS



Anti-static wheels

Ø 200 mm | **802 008 483**

Polyurethane tyres avoiding any risk of sparks.

2 fixed wheels + 2 swivel casters with brakes.



Pneumatic wheels

Ø 200 mm | **802 000 111**

Suitable for uneven or exterior surfaces, load limit 250 kg

2 fixed wheels + 2 swivel casters with brakes.



802 008 420

Handling sheaths for trucks with 1200 x 800 mm base only



862 010 593

Drawbar with return spring Makes trolley handling easier



882 009 649

Hitch + drawbar for link-up, with tow hitch.



Trolleys can be linked together, with cladding adapted to your requirements

