

MESH CLAD CARTS

Models without roof, 2 or 3 drop sides

500 KG

Guarantee
10 years

2 sizes. 1000 x 700 mm or 1200 x 800 mm

For the transport, storage or distribution of your products on trays or loose.

STRUCTURE:

- Entirely mechanically welded frame, strong and long lasting.
- Wire mesh panels in Ø 50 mm gauge offering great freedom of positioning for trays.
- Mechanically welded pushbar at ergonomic height.
- Melamine covered wood tray thickness 16 mm.

FINISH:

- Resistant and durable epoxy paint.

ROLLING QUALITY:

- Wheels Ø 200 mm, 2 fixed + 2 swivel casters with brake, mounted on sealed ball bearings.
- TPE tyres: silent, non-staining, absorb vibration, reduce strain on starting by 50%.

SERVICE :

- Carts delivered assembled and ready for use. (without shelves)

STRONG POINTS

- Especially designed for warehouses, with double access making loading and unloading of goods into and out of the carts easier on both sides.
- Without roof, it allows storage of bulky products high up.




880 007 091



880 005 304 with 2 shelving options

PRODUCT ZOOM

Wood tray shelving option



19mm thick MULTIPLIS wood shelving, 2 positions possible, with or without electro-galvanised rims (21 mm rims).

Height adjustable to accommodate loads.

MWL / shelf: 100 kg

Reference	Features	Pushing height	Tray measurements (W x D) mm	Overall measurementd (WxDxH) mm	Wheels	Weight kg
880 007 091	Wire mesh 2 sides	1015 mm	1,000 x 700	1155 x 705 x 1790	Ø 200 mm grey non-marking	51
880 007 092			1200 x 800	1355 x 805 x 1790		59
880 005 304	Wire mesh 3 sides		1000 x 700	1155 x 705 x 1790		57
880 005 305			1,200 x 800	1355 x 805 x 1790		65

OTHER MODELS AVAILABLE




Wire mesh 3 sides with roof



Fully screened and lockable

OPTIONS



882 005 388 Melamine shelves 1000 x 700 mm
Weight : 6 kg

882 005 389 Melamine shelves 1200 x 800 mm
Weight : 7 kg

SHELVES



882 006 700 Melamine shelves 1000 x 700 mm
Non-slip rubber-coated tray
Weight : 7 kg

882 006 701 Melamine shelves 1200 x 800 mm
Non-slip rubber-coated tray
Weight : 8 kg



862 010 593
Drawbar with return spring

TRACTION



882 009 649
Hitch + drawbar for start-up, with tow hitch.



Trolleys can be linked together, with cladding adapted to your requirements



Pneumatic wheels
Ø 200 mm | **802 000 111**
Suitable for uneven or exterior surfaces, load limit 250 kg



Anti-static wheels
Ø 200 mm | **802 008 483**
Polyurethane tyres avoiding any risk of sparks.



4 swivel castors
Ø 200 mm | **802 010 592**
Replacing 2 fixed wheel as standard by 2 swivel castors.

2 fixed wheels + 2 swivel casters with t 2 fixed wheels + 2 swivel casters with t 4 swivel, 2 with brake