

Astair®

Warranty
3 years



Video
demonstration

Suitable for use in industrial (food processing, pharmaceutical...) and tertiary environments, this compact 32 kg electric lift stacker is distinguished by its lightness and maneuverability. It is suitable for small spaces. Thanks to its various accessories (tray, spur, forks), it facilitates the daily handling of bins, crates, spoils...

Performance

- Rugged design suitable for heavy-duty use.
- Precise height adjustment.
- Equipped with 2 AGM 12v 8Ah batteries with a charging time of 4h for 80% and 12h for 100%. Autonomy of 10h with 10 cycles/h for a 60 kg load.

Ergonomics

- Lightweight design and polyurethane wheels provide great maneuverability and rolling quality on any type of floor including carpet or linoleum.
- Butterfly handles to adjust the hand position to the operator's size.

Security

- Device to prevent the stacker from tipping over in case of obstacles on the descent path.

Warranty

- 3-year warranty excluding worn parts.

Moreover, as nothing should justify throwing away a product under the pretext that it is damaged, we are able to put back in use all the materials of our manufacture and this, without limit of duration.

Complies with the machine directive 2006/42/CE.
Complies with the recommendations of the CRAM R-367.



Equipped with roller spindle

Equipped with tray



Polyurethane wheels with brakes



Battery indicator charger



Equipped with forks



Technical characteristics

| Reference | Capacity * | Lifting speed ** | Lifting rate | Total height | Dimensions L x l | Space between stringers L x l | Weight |
|----------------------|------------|------------------|--------------|--------------|------------------|-------------------------------|--------|
| 8001000609-60 | 60 kg | 125 mm/s | 900 mm | 1200 mm | 845 x 497 mm | 512 x 380 mm | 32 kg |
| 8001000612-60 | | | 1200 mm | 1500 mm | | | 33 kg |
| 8001000616-60 | | | 1600 mm | 1950 mm | | | 35 kg |

* Capacity of the masts at 250 mm according to ISO 3691-5 standard

** Possibility of customised programming

Accessories



Roller spindle

For bore spools Ø 45 mm

Length: 430 mm

Reference: **9310000003-60**



Compact tray

Dimensions: 500 x 500 mm

Reference: **9710000004-60**



Forks for flanged bins

Length: 480 mm

Internal width: 272 mm

External width: 288 mm

Reference: **9610000004-60**